### Irismo™ & Glydea®

**SOLUTIONS FOR MOTORIZED DRAPERIES** 

Irismo™ 45 WireFree RTS | Irismo™ 35 Mini DC | Glydea® 35e | Glydea® 60e

Designed for

# convenience





# IRISMO AND GLYDEA®

## EXPANDS YOUR OPPORTUNITIES

Today, drapery motorization is becoming the standard for hotel rooms, meeting spaces, conference centers and residences. Somfy's Drapery Range offers discreet solutions with flexible power options suitable for any project.

## MAKE ANY SPACE STAND OUT WITH MOTORIZED DRAPERIES



## SOMFY'S COMPLETE DRAPERY MOTOR RANGE:

#### Provides a convenient solution

to reduce glare, energy costs, increase privacy and protect interiors from harmful UV rays.

# Creates a positive user experience that is easy to operate and offers superior, reliable performance.

Compatible with various types of controls from hand-held remotes, a smartphone/tablet app, wireless wall switches, table top controls, sensors, timers, and third-party automation systems.

# Extends the lifespan of draperies by minimizing the damage associated with manual operation.

# Available for all types of draperies such as Pinch Pleat, Ripplefold® and Accordia® to bring any vision to life!

# Enjoy all the benefits of

# motorized draperies

## **AESTHETIC**

- Clean, premium motor design with built-in control modules.
- Easy to conceal behind drapery fabric
- Adjustable limit setting provides precise alignment of drapery fabric.
- Advanced track design and swivel ceiling brackets minimize light gaps.
- Soft start and soft stop drapery motion
- Improved hardware design provides greater overlap and even stack back.



## QUIET

 Motor design and advanced high performance belt drive system provide quiet operation (<44dBA).</li>



• Patented versatile master carrier reduces friction and is adaptable to various drapery types.

• Multiple built-in control options allow seamless

integration with third-party systems.Adjustable drapery speed control



## **EFFICIENT**

- Touch motion feature allows the user to activate the motorized drapery simply by pulling on the fabric.
- Manual override permits the drapery to be adjusted manually.
  This is ideal for power outages and also protects the fabric from damage.
- The "my" function allows user to set a preferred drapery opening which provides enhanced convenience.



## **EASY INSTALLATION**

 Spring loaded one-touch hardware (wall and ceiling mount)

FLEXIBLE

- Motor can be installed to the right or left side of the drapery track.
- Automatic or adjustable limit setting
- Inverse (top mount) option allows the motor to be installed above the track.





# DRAPERY MOTORIZATION POV

# Powered by Somfy

DISCREET. SIMPLE. FLEXIBLE.

(For illustrative purposes only)









# IRISMO™ 45 WIREFREE RTS

### Battery-powered convenience

- Irismo™ 45 WireFree RTS is suitable for any project requirement.
- Tracks up to 33 ft. (10m) with Irismo™ 45 WireFree RTS.
- Wide variety of hardware and accessories for various drapery types including Pinch Pleat, Ripplefold® and Accordia®.

#### Motor dimensions

#### MOTOR WITH BATTERY PACK



#### Features overview

	Irismo™ 45 WireFree RTS Part # 1002353
Motor unit main features	
Soft start	<b>✓</b>
Soft stop	•
Automatic limits on end stop	<b>✓</b>
Manual operation	•
Intermediate position	•
Touch motion with 2 sensitivity settings	•
Adjustable limits	<b>✓</b>
Speed control & adjustment	•
Radio Technology Somfy® RTS	•
Tandem alternative	<b>✓</b>
Sun control	•
Timer control	<b>✓</b>
Installation and setting features	
LED indicators	<b>✓</b>
Audible sound indicator	<b>→</b>
Motor unit direction change	<b>→</b>
Factory reset/programming button	<b>→</b>
Inverse mounting (top mount)	<b>→</b>
Side opening	<b>→</b>
Center opening	·
Asymmetric	<u> </u>
Pinch Pleat	·
Ripplefold <sup>®</sup> with overlap arm	<b>✓</b>
Ripplefold <sup>®</sup> with butt arm	<b>✓</b>
Accordia®	✓

#### Motorized track main characteristics

	Irismo™ 45 WireFree RTS Part # 1002353	
Power supply	26.5V Li-lon	
Average linear speed	87.5 RPM (Default)	
Battery pack	2950 mAh	
Motor sound level	< 44 dBa	
Certifications	CE/cTUV	
Track maximum length	33 ft. (10m)	
Maximum number of junctions	2	
Side opening max weight	99 lbs. (45 kg)	
Center opening max weight	99 lbs. (45 kg)	
Tandem alternative	198 lbs (90 kg)	

#### Track configurations





#### Power accessories





LITHIUM-ION BATTERY PACK (OPTIONAL) #9019741

POWER CHARGER (SOLD SEPARATELY) #1002945

# IRISMOTM 35 MINI DC

### Low voltage solution

- With one track, two motors and various control modules, Irismo™ 35 Mini DC offers a wide range of options for any project requirement.
- Track up to 32 ft. (9m) with Irismo™ 35 Mini DC.
- Available with custom bends and curves.
- Wide variety of hardware and accessories for various drapery types including Pinch Pleat, Ripplefold® and Accordia®.

#### Motor dimensions



#### Features overview


Motor unit main features		
Soft start	<b>~</b>	<b>✓</b>
Soft stop	<b>y</b>	~
Automatic limits on end stop	<b>y</b>	<b>~</b>
Manual operation	<b>✓</b>	<b>✓</b>
Intermediate position	<b>✓</b>	<b>✓</b>
Touch motion with 2 sensitivity settings	•	<b>✓</b>
Adjustable limits	<b>✓</b>	<b>✓</b>
Speed control & adjustment	<b>✓</b>	<b>✓</b>
Dry contact individual, group and master control	<b>~</b>	<b>~</b>
Radio Technology Somfy® RTS	<b>~</b>	
Tandem alternative	<b>~</b>	<b>~</b>
Sun control	•	¥
Timer control	<b>y</b>	<b>~</b>
Installation and setting features		
Setting with buttons on motor unit	•	
Setting with normally open dry contact switch	•	•
LED indicators	<b>y</b>	
Motor unit direction change	<b>&gt;</b>	<b>✓</b>
Factory reset	•	<b>✓</b>
Inverse mounting (top mount)	•	<b>y</b>
Side opening	<b>&gt;</b>	<b>y</b>
Center opening	<b>~</b>	<b>Y</b>
Asymmetric	<b>~</b>	~
Multiple	<b>~</b>	<b>~</b>
Pinch Pleat	<b>y</b>	<b>~</b>
Ripplefold® with overlap arm	<b>~</b>	<b>~</b>
Ripplefold® with butt arm	•	~
Accordia <sup>®</sup>	<b>V</b>	<b>~</b>

Irismo™ 35 RTS | Irismo™ 35 DCT | Part # 1002952 | Part # 1002951

#### Motorized track main characteristics

	Irismo™ 35 RTS Part # 1002952	Irismo™ 35 DCT Part # 1002951
Power supply	24V DC	
Amperage	2 A	
Average linear speed	87.5 RPM	
Power consumption	< 3 W	
Power cable type	4 M (13.2 ft.)	
Control connector type	RJ12	
DCT control circuit voltage	5V DC	
Motor sound level	< 44 dBA	
Certifications	CE	
Track maximum length	32 ft. (9.7 m)	
Maximum number of junctions	2	2
Minimum bending radius	11.8 in.	(30 cm)
Minimum curving radius	118 in. (	300 cm)
Side opening max weight	77 lbs.	(35 kg)
Center opening max weight	77 lbs.	(35 kg)
Tandem alternative	154 lbs.	(70 kg)

#### Other available track shapes



#### Power accessories



# GLYDEA®

### Adaptable and Universal

- With one track, two motors and various control modules, Glydea® offers a wide range of options for any project requirement.
- Track up to 36 ft. (10.9m) wide with Glydea® 60e and up to 32 ft. (9m) with Glydea® 35e.
- Available with custom bends and curves.
- Wide variety of hardware and accessories for various drapery types including Pinch Pleat, Ripplefold® and Accordia®.

#### Motor part numbers

	Glydea® 35e	Glydea® 60e
Control Option		
DCT motor with 10' cable and molded NEMA plug	Part # 1002465	Part # 1002545
RTS motor with 10' cable and molded NEMA plug	Part # 1001615	Part # 1001617
RS485 motor with 10' cable and molded NEMA plug	Part # 1002109	Part # 1002108
Wired motor without plug	Part # 1002464	Part # 1001537

#### Motor dimensions



#### Features overview

Soft start Soft stop


3011 Stop	•
Automatic limits on end stop	<u> </u>
Manual operation	<b>~</b>
Intermediate position	<b>~</b>
Touch motion with 2 sensitivity settings	<b>~</b>
Adjustable limits	<b>~</b>
Speed control & adjustment	<b>~</b>
3 normally open dry contacts	<b>~</b>
2 normally open dry contacts	<b>~</b>
2 normally open dry contact sequencing mode	<b>✓</b>
Dry contact individual, group and master control	<b>~</b>
Radio Technology Somfy® RTS	<b>✓</b>
Infrared	<b>✓</b>
RS485 digital technology infrared	<b>✓</b>
Z-Wave®	<b>~</b>
ZigBee®	<b>~</b>
Tandem alternative	<b>~</b>
Sun control	<b>~</b>
Timer control	<b>✓</b>
Setting with buttons on motor unit	<b>✓</b>
Setting with normally open dry contact switch	<b>~</b>
LED indicators	<b>✓</b>
Motor unit direction change	<b>✓</b>
Factory reset	<b>✓</b>
Inverse mounting (top mount)	<b>✓</b>
Side opening	<b>V</b>
Center opening	<b>✓</b>
Asymmetric	<b>✓</b>
Multiple	<b>Y</b>
Pinch Pleat	<b>✓</b>
Ripplefold® with overlap arm	<b>✓</b>
Ripplefold® with butt arm	<b>✓</b>
Accordia <sup>®</sup>	<b>~</b>

Glydea® 35e Glydea® 60e

#### Motorized track main characteristics

	Glydea® 35e	Glydea® 60e
Power supply	110 V AC 50/60 HZ	
Amperage	0.5 A	1 A
Average linear speed	4.9"/s-7.86"/s 12.5 cm/s to 20 cm/s	
Power consumption	60 W	120 W
Power cable type	3-wire cable with molded NEMA plug 4-wire cable (wired version only)	
Control connector type	RJ12	
DCT control circuit voltage	3.3V DC	
Motor sound level	< 44 dBA	
Certifications	c TUV us, CCC, CE	
Track maximum length	32 ft. (9.7 m)	36 ft. (10.9 m)
Maximum number of junctions	2	
Minimum bending radius	11.8 in. (30 cm)	
Minimum curving radius	118 in. (300 cm)	
Side opening max weight	77 lbs / 19.6 ft 35 kg / 6 m	132 lbs / 19.6 ft 60 kg / 6 m
Center opening max weight	77 lbs / 19.6 ft 35 kg / 6 m	132 lbs / 19.6 ft 60 kg / 6 m
Tandem alternative	154 lbs / 70 kg 64 ft / 19.4m	264 lbs / 120 kg 72 ft / 21.8 m

#### Other available track shapes



#### Power accessories



	Glydea® 35e	Glydea® 60e
Power supply	110 V AC 50/60 HZ	
Amperage	0.5 A	1 A
Average linear speed	4.9"/s-7.86"/s 12.5 cm/s to 20 cm/s	
Power consumption	60 W	120 W
Power cable type	3-wire cable with molded NEMA plug 4-wire cable (wired version only)	
Control connector type	RJ12	
DCT control circuit voltage	3.3V DC	
Motor sound level	< 44 dBA	
Certifications	c TUV us, CCC, CE	
Track maximum length	32 ft. (9.7 m)	36 ft. (10.9 m)
Maximum number of junctions	2	
Minimum bending radius	11.8 in. (30 cm)	
Minimum curving radius	118 in. (300 cm)	
Side opening max weight	77 lbs / 19.6 ft 35 kg / 6 m	132 lbs / 19.6 ft 60 kg / 6 m
Center opening max weight	77 lbs / 19.6 ft 35 kg / 6 m	132 lbs / 19.6 ft 60 kg / 6 m
Tandem alternative	154 lbs / 70 kg	264 lbs / 120 kg

#### DecoFlex WireFree™ RTS Table Top **Sunis Indoor**

Single to Five Channel table top accessory Switch sold separately

Silver

1810632 1810633 1810639 1810641 1810650 1810652

Easily adapt to RTS technology with the RTS plug-in module.

Telis RTS Hand-held Remotes

Single Channel and Five Channel

hand-held remotes



1811185 1810972 1811051

## WireFree™ RTS

With over 10 million installations worldwide, RTS has become the standard for secure radio technology in the industry.

Allows automatic operation of motorized draperies based on the amount of sunlight



9013707

## remote with on-screen display



Telis 1 Chronis RTS Timer

Single Channel timer and

RADIO TECHNOLOGY SOMFY® (RTS)

Pure Silver 1805237 1805238

#### Telis 16 RTS Transmitter 16 Channel hand-held remo



Pure Silver 1811081 1811082

ThermoSunis Indoor

and temperature in a room.

9013708

WireFree™ RTS

#### Smoove® 1 RTS Pure

Single channel, surface mounted, wireless wall control compatible with 7



Pure



Additional

Frame Options



1811533





DecoFlex WireFree™ RTS

Single to Five Channel wireless wall

switches, available with custom

Ivory

1810897 1811072 1810830

#### Universal RTS Interface

16-channel interface allows users to convert RS232, RS485, and infrared commands into

Easily integrates with third-party



1810872

#### Somfy myLink™

Control draperies while home or away using your tablet or smartphone. A simple on-screen setup wizard helps users create timed events, scenes and more.

For more information on RTS, please visit somfysystems.com/RTS





INTEGRATION OPTIONS Integration options not compatible with Irismo™ 45 WireFree RTS.



Compatible with iOS and Android





#### WIRED CONTROL





1800219



#### DRY CONTACT



**ZigBee**®

Easily integrates with ZigBee® systems using the ZigBee® plug-in module.



**Z-Wave**®

1870228





Easily integrates with Z-Wave® systems using the Z-Wave® plug-in module.



Digital Network systems using the RS485 plug-in module.

1811129

# Easily integrates with Somfy

**SOMFY**<sup>®</sup> is the leading global manufacturer of strong, quiet motors with electronic and app controls for interior and exterior window coverings. Over 270 million users worldwide enjoy the more than 150 million motors produced by Somfy. During the past 40+ years, Somfy engineers have designed products for both the commercial and residential markets to motorize window coverings such as interior shades, wood blinds, draperies, awnings, rolling shutters, exterior solar screens and projection screens. Somfy motorization systems are easily integrated with security, HVAC and lighting systems providing total home or building automation.

#### SOMFY SYSTEMS INC SOMFY NORTH AMERICAN HEADQUARTERS

121 Herrod Blvd. Dayton, NJ 08810

P: (800) 22-SOMFY (76639)

NJ: (609) 395-1300 F: (609) 395-1776

#### **FLORIDA**

6100 Broken Sound Pkwy. N.W.

Suite 14

Boca Raton, FL 33487

P: (800) 22-SOMFY (76639)

F: (561) 995-7502

#### **CALIFORNIA**

15291 Barranca Parkway Irvine, CA 92618-2201

P: (800) 22-SOMFY (76639)

F: (949) 727-3775

#### SOMFY ULC SOMFY Canada Division

5178 Everest Drive

Mississauga, Ontario L4W2R4

P: (800) 66-SOMFY (76639)

CN: (905) 564-6446

F: (905) 238-1491

www.somfysystems.com

A BRAND OF **SOMFY** GROUP





