Automatic

Swing Gate Operators

powerful & silent







Sliding gate



Cantilever sl. gate sys.



Swing gate operators



Garage doo operators



Barrier operators



El. gate contro



Impulse emitters



Safety devices



1iscellaneous

tousek TURN und TURN UP



Electromechanical operator for all types of residential swing gates





Emergency release lock

All operators of the series Turn are equipped with a release lock, enabling the manual opening and closing of the gate in the event of a power failure. In model Turn-up the release lock can be closed with a key.



Easy installation

With their motor consoles, which can be screwed and in particular adjusted, the Turn and the Turn-up can be installed in nearly



Long useful life

The stainless piston rod, the aluminium casing and the massive steel spindle guarantee a long operation.



The operator unit of the series Turn

all components are made of metal and the axles are resting on ball bearings.



Turn operators can be used for all swing gate models (see technical data). Even doors opening outwardly or rising gates (with optional operator console) can be automated with the series Turn.

Soft stop

Turn, in combination with the control unit ST51, closes the gate very silently and softly


The control unit

The technically innovative microprocessor control unit ST 51 has been developed especially for electromechanical swing gate operators Turn. This modern motor control unit of the latest generation regulates all functions and consists of various connection possibilities for e.g. radio, code switch, switch for intercom system and all usual gate security systems.



Two line display

All functions, like impulse operation/automatic operation, partial opening, soft stop etc can be easily adjusted in a German plaintext menu by the means of easily accessible switches and can be therefore adapted to all gates.



■ Powerful 230V motor ■ Adjustable soft stop (motor control) ■ Until approximately 350kg gate weight ■ 3,0m wing weidth

max 110° opening angle

In order to achieve an extremely long useful life under all application conditions, the spindle is made of stainless steel and the casing is made of aluminium. The self-blocking spindle blocks the gate in each position and therefore no additional locking device is required.*) It can be easily released by hand in the event of a power failure.



D	TUDN 40	TURN 00		
Designation	TURN 10	TURN 20	TURN UP1	TURN UP2
Motor position	below	below	above	above
Max gate panel weight	350kg	350kg	350kg	350kg
Max gate panel width	2,5m	3m	2,5m	3m
Cycles/day	20	20	20	20
Motor voltage	230V+/-10%	230V+/-10%	230V+/-10%	230V+/-10%
Gate travel speed	18,5mm/sec.	18,5mm/sec.	18,5mm/sec.	18,5mm/sec.
Max pulling power	3500N	3500N	2800N	2800N
Max travel stroke	303mm	402mm	300mm	400mm
Max opening angle	95°	110°	95°	110°

Note: Please be aware that the gate-security devices shown in this brochure are examples and are not to be considered as guidelines with regard to applicable standards. The standards in effect in each country must be complied without fail during start-up and/or installation

Please check the technical data sheets for more detailed information. All rights reserved.

*) In order to achieve a fixed locking, it can be necessary, according to the installation situation, to install an electric lock.

www.tousek.com



tousek PRODUCTS

- Sliding-gate operators
- **Swing-gate operators**
- **Garage-door operators**
- Folding-gate operators
 - Barriers A
 - Parking systems
 - **Electronic controls**
- **Radio remote controls**
 - Kev switches
 - Access control
 - **Security devices**

tousek Ges.m.b.H. headquarters

A-1230 Wien, Zetschegasse 1 Tel: +43/ 1/ 667 36 01 Fax: +43/ 1/ 667 89 23 Email: info@tousek.at

tousek GmbH

D-83395 Freilassing Traunsteiner Straße 12 Tel: +49/ 8654/ 77 66 - 0 Fax: +49/ 8654/ 57 196 Email: info@tousek.de

tousek Gmbh

CH-6275 Ballwil Bahnhofstraße 14 Tel: +41 41/448 29 65 Fax: +41 41/448 29 66 Email: info@tousek.ch

tousek Benelux NV

B-3930 Hamont-Achel Buitenheide 2A / 1 Tel: +32 11 91 61 60 Fax: +32 11 91 61 60 Email: info@tousek.nl

tousek Sp. z o.o.

PL-43-190 Mikołów (k/Katowic) Gliwicka 67 Tel: +48/ 32/ 738 53 65 Fax: +48/ 32/ 738 53 66 Email: info@tousek.pl

tousek s.r.o.

CZ-130 00 Praha 3, Jagellonská 9 Tel: +420/ 222 090 980 Fax: +420/ 222 090 989 Email: info@tousek.cz

For many years now,

we have been working on developing gate operators and their accessories at the forefront in the international field. Expertly trained employees and comprehensive service are two of the factors in satisfying customers' wishes.



tousek - the original

The **Original tousek Quality** certificate is your absolute guarantee of the highest quality when you purchase a **tousek** operator.



Reliable and secure

Tousek's leading technical development, including the Rolling Code Radio System, for instance, which generates a new radio code every time the remote control is activated, thus preventing the radio signal from being scanned by unauthorised persons, is your guarantee of greater security, in demand today as part of seamlessly protecting property. The quality of **tousek** products is guaranteed by the most stringent tolerances in manufacture and constant monitoring.

Compatibility

Tousek places great emphasis on keeping all elements of the gate operator, accessory and security programmes compatible as the assortment of products grows.





www.tousek.com

Your tousek partners will be happy to advise you personally.





tousek garage doors operators convenient and safe



tousek barrier systems attractive and robust



tousek sliding-gate operators compact and safe



tousek impulse emitter programmes compatible and secure



www.tousek.com

Visit our website for more important information all about automatic operators.